

# Rittal – The System.

Faster – better – everywhere.



## SK 3120.200 Speed control

State: 03/10/2022 (Source: [rittal.com/com-en](http://rittal.com/com-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SK 3120.200 - Speed control For fan-and-filter units and air/air heat exchangers

Temperature-dependent speed control to minimise noise and save energy in part-load operation.

## Features

Model No.	SK 3120.200
Product description	Temperature-dependent speed control to minimise noise and save energy in part-load operation.
Supply includes	Speed control NTC sensor, length 1.80 m
Speed	100 %
Note	Only suitable for use with single-phase AC motors and equipment Not suitable for EC motors
Technical specifications	For mounting on a 35 mm support rail EN 50 022 Phase cross-over with microcontroller Maximum fan output 300 W or 2 A
Dimensions	Width: 105 mm Height: 90.5 mm Depth: 60.2 mm
Setting range	20 °C...55 °C
Rated operating voltage	100 V - 230 V
Packs of	1 pc(s).
Weight/pack	0.36 kg
Copper weight (kg per piece)	0
Customs tariff number	90321020
EAN	4028177631441
ETIM 7.0	EC000256
ECLASS 8.0	27142320

# Approvals

---

Approvals

UR

---

Certificates

EAC

---

Explanations

Declaration of conformity

Declaration of conformity UK